

ACCESS PANEL

Easily removable for on-the-spot maintenance and service.

INTEGRATED HANDLES

DIGITAL CONTROLS

FILTER COMPENSATION

A variable speed fan adjusts to maintain airflow and uphold humidity control.

ENGINEERED FOR MAXIMUM EFFICIENCY.

QUEST 335


- + THE MOST EFFICIENT DEHUMIDIFIER AT 9.3 PTS/ KW H
- + 335 PINTS AT 80° (26.7°C)/60% RH
- + 32.9”W X 24.4”H X 23.5”L (83.6CM X 62CM X 59.7CM)
- + PATENTED MULTI-COIL TECHNOLOGY
- + MERV-13 FILTRATION
- + 5-YEAR WARRANTY

Quest 335

High-Efficiency Dehumidifier



Unit:	Quest 335 4042500
Impeller:	Backward curved
Power (Watts):	1565
Supply voltage:	208-230 VAC - 1 Phase - 60 Hz.
Current Draw (Amps):	7.9A @208v 6.9A @ 230v
Rated Current Draw (Amps): (104°F 36%)	10.3A @ 208v 8.8A @ 230v
Minimum Circuit Ampacity (MCA):	15.8A @ 208v 14.4A @ 230v
Maximum Overcurrent Protection (MOP):	25A @ 208v 20A @ 230v
Energy Factor (L/kWh):	4.3
Operating Temp:	56°F Min - 95°F Max
Water Removal (Pints/Day):	335
Efficiency (Pints/kWh):	9.3
Air Filter (MERV-13):	Size: 20" x 22" x 2"

Power Cord:	 NEMA 6-15P	
Drain Connection:	3/4 Threaded NPT	
Refrigerant Type:	R410A	
Refrigerant Amount:	4lb. 12oz.	
Dimensions:	Unit	Shipping
Width:	32.9"	36"
Height:	24.4"	30"
Length:	23.5"	28"
Weight:	215 lbs	255 lbs

* requires buck/boost transformer to run on 277V

